

# VISION

## AV-3000 INTEGRATED AUDIO SYSTEM

THE COMPLETE AUDIO SOLUTION PLUS USB HUB

### 2 x 20w (RMS)

A powerful 2 x 20w amplifier in the master speaker gives you plenty of volume in classroom and training room environments

### 2-WAY FULL RANGE DRIVERS

Delivers clear sound with a wide frequency response, with a broad dispersion to make sure everybody in the audience gets the message

### BATTLE-READY

Rugged MDF construction, a metal grille, and a secure control panel deters vandalism

### CABLES INCLUDED

1 x 4m multipin cable to connect the control panel to the master speaker, and 1 x 5m speaker cable to connect the slave speaker to the master speaker

### FLUSH-MOUNTING SPEAKERS

A flush-mounting speaker bracket is included with a fall-arrest safety cable

### 3 STEREO INPUTS INTO BREAK-AWAY CONTROL PANEL

The control panel is connected to the master speaker via one cable. You can mount the control panel to the backbox provided, or into dado trucking or a flush-mount wall box

### COLOUR-CODED

The silver speakers are designed to sit each side of an Interactive Whiteboard, and blend in with the board's bezel



### INTERNAL POWER

Comes with long UK and Euro power cable

### SCALLOPED CONNECTION PANEL

Because the speakers fit flush to the wall, the AV-3000 has a hollow section to allow easy connection of cables

### PROJECTOR REMOTE HIDEAWAY SLOT

The slave speaker features a handy slot to hide data projector remote controls. Only fits 'credit-card style remotes'



### BUILT-IN 1:2 USB HUB

For convenience, the AV-3000 features a USB hub allowing easy access of a USB port when the PC is not accessible. USB is connected from the PC to the rear of the control panel. USB access is then available on the front of the control panel and on the rear of the master speaker

# AV-3000 INTEGRATED AUDIO SYSTEM

<b>SPECIFICATIONS:</b>	<b>LOUDSPEAKER DIMENSIONS</b>	350 x 115 x 110mm
	<b>CONTROL PANEL DIMENSIONS</b>	146 x 86 x 58mm
	<b>CARTON DIMENSIONS</b>	420 x 395 x 165mm
	<b>PACKAGED WEIGHT</b>	7.65kg
	<b>COLOUR</b>	Loudspeakers: Silver Control Panel: Dark Grey and White (RAL9010)
	<b>INPUTS</b>	1 x Multipin cable 4m long 1 x Unshielded Speaker cable 5m long 2 x Wall Brackets with safety tether
	<b>TECHNICAL DETAILS</b>	2 x 20w @ 8Ω Total Harmonic Distortion ≤2% (80H-12.5kHz) Frequency response (line in): 80Hz-12.5kHz(±2dB) Signal to noise ratio (line in): ≥60dB (A-weighted) Rating input level/Impedance: line in 500mV/47kΩ Power consumption (rating condition): ≤80W
	<b>ACCESSORIES INCLUDED</b>	1 x Multipin cable 4m long 1 x Unshielded Speaker cable 5m long 2 x Wall Brackets with safety tether 1 x IEC cable with IK/Euro adaptor plug 5m long
	<b>POWER RATING</b>	230V Internal Power Supply
	<b>RECOMMENDED PALLET QUANTITY</b>	60
	<b>WARRANTY</b>	2-year return to base
	<b>COMPLIANCES</b>	RoHS, WEEE & CE compliant UL
<b>ORDER PART CODE</b>	AV-3000	

**Control Panel:**



**Master Speaker Connection Panel:**



Because we are committed to improving our products the spec of this product may change without warning.

**VISION**

installation:innovation

www.vision-displays.com T +44 (0)870 600 9300